



# PMI - 50 TL3 Factsheet

Microplasma - The ideal solution for welding thin sheets with a thickness of up to ~ 1mm. The lowest adjustable welding current is 0,2 Ampere.

## TECHNICAL DETAILS

The arc is constricted by a copper nozzle, which results in a high power density. The concentrated arc, in conjunction with the controllable plasma gas, enables higher welding speeds and deeper penetration (root welding) to be achieved, which saves time and money. The strong bundling of the arc and the welding speed mean that only a narrow heat-affected zone is formed, which results in less thermal distortion in the component.

<b>Applicable Welding Methods</b>	<ul style="list-style-type: none"> <li>• PLASMA Seam Welding</li> <li>• PLASMA Brazing</li> <li>• PLASMA Coating</li> </ul>
<b>Range of suitable material thickness (Plasma seam welding)</b>	~ 0.1 – 1 mm
<b>Automation</b>	• Capable for automation
<b>Operating modes</b>	DC
<b>Supply Voltage</b>	230 V ±15 % 50/60Hz
<b>Phase</b>	1 Phase
<b>Power connection</b>	Gardy plug, 2.5 mm <sup>2</sup>
<b>Max. welding current at 35 % duty cycle (40 °C)</b>	50A
<b>Max. welding current at 100 % duty cycle (40 °C)</b>	30A
<b>Adjustment range welding current</b>	0.2 – 50 A
<b>Max. pilot current at 35 % duty cycle (40 °C)</b>	15A
<b>Max. pilot current at 100 % duty cycle (40 °C)</b>	15A
<b>Adjustment range pilot current</b>	0.5 – 15 A
<b>Adjustment range TIG mode</b>	0.5 – 50 A
<b>Cooling</b>	Liquid
<b>Degree of protection</b>	IP 21 S
<b>Length</b>	620mm
<b>Width</b>	300mm
<b>Height</b>	555mm
<b>Weight</b>	47kg
<b>Features</b>	<ul style="list-style-type: none"> <li>• Power source with HF-ignition</li> <li>• USB interface</li> <li>• Ethernet interface</li> <li>• Integrated welding program memory</li> <li>• Integrated monitoring / gaging of cooling medium</li> <li>• Integrated electronic gas regulation (PGR)</li> <li>• Integrated cooling</li> <li>• Integrated automation interface</li> <li>• Software for external controlling via computer (diagnostics, parameter setup, documentation)</li> <li>• Flowmeter plasma gas</li> <li>• Flowmeter shielding gas</li> <li>• Foot control of the current</li> <li>• Remote Control RC-S</li> <li>• Touch Screen 7,0"</li> <li>• Pilotinverter with HF-ignition</li> </ul>
<b>Automation Interface "Tiny"</b>	• Included
<b>Digital Inputs</b>	4 × 24 V
<b>Digital Outputs</b>	4 × 24 V
<b>Analog Inputs</b>	2 × 0 – 10 V
<b>Analog Outputs</b>	2 × 0 – 10 V
<b>CAN Bus (SBI protocol)</b>	• Included
<b>Capability for / availability of specific bus interfaces</b>	• Included

## Torches Recommended for Use

SBI GmbH - Gewerbering 15 - A-3710 Ziersdorf

[www.sbi.at](http://www.sbi.at)

Phone: +43/29 52/341 39  
Fax: +43/29 52/341 39-800  
Mail: [office@sbi.at](mailto:office@sbi.at)

VAT-no.: ATU 74592719  
Commercial register no.: FN 515241 h  
LG: Korneuburg

Bank details: Raiffeisenbank Wels eGen  
Bank code: 34680  
Account no.: 60.2862

BIC/SWIFT: RZOOAT2L680  
IBAN: AT25 3468 0000 0060 2862  
EORI: ATE OS1 000 098 938

## About SBI GmbH

SBI was founded in 1999 with the aim of developing rapid prototyping technologies. SBI has therefore developed its plasma technologies and built welding solutions. From automated solutions for coating technologies to the repair of forging dies or plasma arc deposition machines for the maintenance of aircraft turbines, SBI has established world-renowned references in the field of arc deposition plasma. Since 2009, SBI has established itself as the main supplier of its plasma-based technology for the 3D manufacturing of aeronautical parts.

Besides its renown portfolio of superior plasma inverter systems and plasma welding equipment, SBI has been developing its own additive manufacturing machines. The manufacturer put the metal additive manufacturing system M3DP on the market in 2019.

